




Installation & Removal Procedure :



- 1 Remove chains from the bag. Unhook the flexible hoop & spread the chains out on the road. Ensure there are no twists or tangles in the chains, this step is important for ease of fitting.



- 4 Connect the side chain & red hook together on the front top of the wheel, then make sure to push the flexible cable right over to the back of the tyre wall.



Check the flexible cable is running evenly around the inside of the tyre. (Important)



- 2 Pass the yellow end of the flexible cable around the back of chains touching the tyre in this step, so you chain between the tyre & the road.



- 5 Connect the tension chain with rubber hook to the autolocking lever at the bottom of the wheel & tighten firmly.

If there is not enough tension chain left for retightening, go back to step 4 & connect 2nd or 3rd link of the side chain onto the red hook.
Check the side chain is running evenly around the sidewall of the tyre, this ensures the flexible hoop on the inside of the tyre is doing the same.
Pass the rubber hook through one or both red loops on the side chain and secure firmly.



- 3 Pick up the ends of the flexible cable and join them together on the top of the tyre. Try to keep the chain links in front of your hands as in the photo so they do not drop behind the wheel.

Autolocking Lever



- 6 Once these steps have been completed and the chains are evenly and firmly fitted to each of the drive wheels, drive forward slowly for 20 mtrs to bed the chains in, then retighten firmly.

Removal of Chains

To remove the chains stop each wheel in the same position the chains were fitted, the autolocking lever at the bottom of the wheel as in the photo, then simply reverse the installation steps in order.

When you have disconnected the chain off the tyre make sure it is laying flat on the road, then drive forward to clear the chains.

PLEASE NOTE: While driving in the snow with chains fitted you must drive carefully, avoid sudden acceleration or sudden stops and never exceed 50 km/h.

Warning: Failure to fit chains firmly & correctly could result in damage to vehicle & chains.

Snowchains.com.au

Give your vehicle and family the protection they need
hire or buy only quality snow chains

1300 135019